



*The Mark of the professional...*

## CSS-50 SPEAKER SYSTEM

### INSTALLATION INSTRUCTIONS

- 1.) Determine speaker location.
- 2.) Remove ceiling tile in that location, and adjacent tile.
- 3.) If installing in 2' by 4' grid, add a cross tie to make a 2' by 2' space for speaker mounting.
- 4.) Carefully remove the white grille from the speaker cabinet (it is held on with 4 velcro tabs).
- 5.) Lay white grille in 2' by 2' ceiling grid. Handle white grille by edges to prevent soiling white grille cloth.
- 6.) Lay black speaker cabinet on white grille. Both grille and cabinet should lay in ceiling grid.
- 7.) Screw the four eye bolts into the four T-nuts on back of cabinet and attach safety chain/cable.
- 8.) Connect leads to two lug terminal strip on rear of cabinet. (Positive to red—negative to other)
- 9.) Replace ceiling tile(s).

## NOTICE

To comply with J. W. Davis & Company warranty and for safe installation, it is recommended that a safety chain/cable be attached to the four eye bolts located on the back of the CSS-50 cabinet.

NEW TECHNOLOGY  OLD RELIABILITY

*J. W. Davis & Company*

3030 Canton Street | P.O. Box 710219 | Dallas, Texas 75371-0219

Sales 800-527-5705 | Sales Fax 800-388-9106 | Corp 214-651-7341 | Corp Fax 214-939-0328 | [www.jwd.com](http://www.jwd.com) | [jwd@jwd.com](mailto:jwd@jwd.com)