

J.W. DAVIS RAW SPEAKERS

LOUDSPEAKERS






CONSISTENT QUALITY ASSURED

Only the highest grade of materials are used in Davis loudspeakers. Consistency is maintained by extensive TEF[®] testing before the speakers are accepted into our warehouse. You can be assured that you will receive the same high quality every time you order a Davis speaker.

GET THE SPEAKER YOU NEED... WHEN YOU NEED IT

A wide variety of models and large in stock quantities insure availability as your needs arise. Our "same day" shipping policy guarantees prompt delivery.

Quality You Can Hear...

8"  DS-805 10 watt General Purpose	8"  DSWP-805 12 watt Water Resistant	8"  DS-805/45 10 watt 45 Ohm
8"  DS-810 20 watt General Purpose	8"  DS-810DC 12 watt Dual Voice Coil	8"  DSC-820 20 watt General Purpose
5"  DS-505 10 watt General Purpose	5"  DS-505/16 10 watt 16 Ohm	5"  DS-510 20 watt General Purpose
5"  DS-510-16 20 watt 16 Ohm		

SPECIFICATIONS FOR DAVIS SPEAKERS

Model Number	Diameter	Impedance (Ohms)	Power Rating	Frequency Rating (Hz)	Resonant Frequency (Hz)	Magnet Weight (Ounces)	Voice Coil	Sensitivity (1w 1m)	Speaker Depth (Inches)	Shipping Weight (Pounds)	Number Per Carton	Recommended Use & Special Features
DS-805	8"	8	10	70-16,500	85	5.3	1"	95 dB	2 ⁵ / ₈	20	12	General purpose, full range. Use with SBA system.
DSWP-805	8"	8	12	60-8,000	125	5.5	3/4"	90 dB	2 ³ / ₄	27	16	Water resistant, general purpose, sealed voice coil
DS-805-45	8"	45	10	80-15,000	90	5.3	1"	95 dB	2 ⁵ / ₈	20	12	45 Ohm, General Purpose
DS-810	8"	8	20	70-14,000	69	10	1"	95 dB	3	27	12	Greater power, full range, general purpose
DS-810DC	8"	8	12	60-12,000	75	10	1"	92 dB	2 ⁷ / ₈	45	16	Twin voice coils for simultaneous music and paging or stereo
DSC-820	8"	8	20	70-17,000	90	10	1"	93 dB	3 ¹ / ₄	43	16	General purpose
DS-505	5"	8	10	70-16,000	130	10	1"	90 dB	2 ¹ / ₄	32	16	General purpose, full range, no whizzer
DS-505/16	5"	16	10	70-16,000	130	10	1"	89 dB	2 ¹ / ₄	32	16	General purpose, full range, no whizzer, 16 Ohm
DS-510	5"	8	20	150-16,500	110	10	1"	91 dB	3/4	23	12	Greater power, full range, no whizzer
DS-510/16	5"	16	20	100-14,000	110	10	1"	90 dB	2 ¹ / ₄	23	12	General purpose, 16 ohm, no whizzer

NEW TECHNOLOGY  OLD RELIABILITY

J.W. Davis & Company

3030 Canton Street • P.O. Box 710219 • Dallas, Texas 75371-0219

Sales 800-527-5705 • Sales Fax 800-388-9106 • Corp 214-651-7341 • Corp Fax 214-939-0328 • www.jwd.com • jwd@jwd.com